

# Technical Datasheet

## Green Wallbox 2 Pro Slim



### Electrical Specifications

Charging power	7,4kW	11kW	22kW
Rated voltage	230V	400V	400V
Rated Current	32 A (1P)	16 A (3P)	32 A (3P)
Connector Type	Type 2	Type 2	Type 2
Cable Width	3x6mm <sup>2</sup>	5x2,5mm <sup>2</sup>	5x6mm <sup>2</sup>
Configurable Current	from 6A to 32A	from 6A to 16A	from 6A to 32A
Rated Frequency	50 Hz / 60 Hz		
Protection Rating	IP65 / IK08		
Surge Category	CAT III		
Residual Current Detection	AC 30mA / DC 6mA		
RCCB	External RCCB may be required (Type A or B according to local regulations)		

### General Specifications

Model	2 Pro Slim
Colour	Black
Cable lenght	6 / 10 m
Charging mode	Mode 3 (IEC 61851-1)
Weight	1,65kg (without cable)
Operating temperature	-25 °C to 40 °C
Storage temperature	-40 °C to 70 °C
Standards	CE mark (LVD 2014/35/EU, EMCD 2014/30/EU) IEC 61851-1, IEC 61851-21-2, IEC 62196-1, IEC 62196-2

### UI & Communications

Connectivity	Wi-Fi, Bluetooth
User Identification	Green Wallbox App (iOS, Android), NFC Cards
User Interface	Green Wallbox App (iOS, Android)
Charger Status Information	RGB LED, Green Wallbox App (iOS, Android)

Green Wallbox Sp. z o.o.  
ul. Limanowskiego 3/24, Kraków 30-551  
www.greenwallbox.com

### Dimensions



### SKU Structure

1	Manufacturer	GW	Green Wallbox
2	Device type	WBX	Wallbox
3	Model	2PS	2 Pro Slim
4	Power	74	7,4 kW
		11	11 kW
		22	22 kW
5	Outlet	6	6 meters Type 2 Plug
		10	10 meter Type 2 Plug